

## Metso Lokotrack® LT200HP™

# Compact mobile cone crusher

Lokotrack® LT200HP™ mobile cone crusher is especially suitable for contractors needing versatile aggregate production. Ideal for road construction, railroad ballast, asphalt, and concrete fractions, it features the proven Nordberg® HP200e™ cone crusher. The latest model offers at least 15% fuel savings over the previous hydraulic-driven version, thanks to its efficient direct belt drive.

### High capacity HP200e cone crusher

Proven crusher suitable for hard rock  
Excellent end product quality (e.g. concrete aggregates)  
Different cavities for secondary or tertiary applications  
Max feed size 200 mm (8")

### H10-6 lifting conveyor

Adjustable speed for easy material control  
Equipped with metal detector  
Hopper back wall can be opened for lower feeding height.  
Discharge end is hydraulically lowered for transport.

### IC process control for connectivity

Radio remote for feeder control and tracking  
Remote IC app for improved safety and productivity  
Metso Metrics for remote process monitoring

### Robust H8-10 or H8-12 main conveyor

Hydraulic driven belt conveyor  
Extended conveyor for more discharge height

### Fuel-efficient CAT® C9.3B power transmission

Direct drive for crusher with purposely designed gearbox and hydraulic clutch for high reliability  
Optimized hydraulics efficiency  
Reduced hydraulic oil volume 215 l (57 gal)

### Heavy-duty tracks and frame

FEM designed structure for optimized weight and lifetime  
Open frame design for easy service access  
Agile tracks with 2-speed mode for turnability and speed



## Technical specifications

Transport dimensions		
Weight	32,000 kg	71,000 lbs
Length	16,800 mm	55'
Width	3,000 mm	9' 10"
Height	3,400 mm	11' 2"
Feeder		
H10-6		
Hopper volume	5 m <sup>3</sup>	6.5 yd <sup>3</sup>
Loading height	2,700 mm	8' 10"
Loading width	2,440 mm	8' 0"
Crusher		
Nordberg® HP200e™		
Feed opening	200 mm	8"
Drive type	Direct	Direct
Nominal power	160 kW	215 hp
Process control	IC	IC
Main conveyor		
H8-10 / H8-12		
Width	800 mm	31,5"
Length	10,000 / 12,000 mm	32' 10" / 39' 4"
Discharge height	2,900 / 3,630 mm	9' 6" / 11' 11"
Power unit		
CAT® C9.3B		
Power	310 kW	416 hp
Fuel /hydr.oil vol.	630 / 215 l	166 / 57 gal
Options		
Additional service platform	Hydraulic Power Takeoff	
Climate kit (hot/cold)	Interlocking cable	
Discharge hood for main conveyor	Lifting conveyor feed chute	
Dust encapsulation for conveyors	Metso Metrics	
Extended main conveyor	Pre-heater for diesel engine	
Filter kit	Remote IC	
Fuel filling pump	Remote radio control	
High pressure water spraying	Safety package	
Hydraulic generator	Special scraper for conveyors	



See it in 3D at  
[live.metso.com](http://live.metso.com)

### Applications



Road construction



Railroad ballast



Asphalt and concrete  
fractions

### Combine with

- LT96 and LT106 jaw crushers
- LT200HPS and LT220D cone crushers
- LT7150 VSI crusher
- ST2.3, ST3.8 and ST4.8 mobile screens