

TECHNICAL DATA

TAMPER

BVT 65



Reliable and long lasting

Engine protection, fuel filter, automatic oil level control



More transparency

Hour meter RPM-meter with service indicator (optional)



Simple operation

Engine and fuel supply with combined switch


Shipping dimensions in m3
BVT 65 0,262

Standard Equipment

- ✓ Engine Protection System
 - Protective engine covering
 - Automatic oil level control
 - Dual fuel filter system
- ✓ Vibration insulated steering handle
- ✓ Self-cleaning air filter housing
- ✓ Protective covering
- ✓ Single point lifting device
- ✓ Recoil starter
- ✓ Plastic castor as loading aid
- ✓ Infinitely variable frequency
- ✓ Combination of engine stop/fuel switch
- ✓ 3-2-1 Warranty

Optional Equipment

- Transport device with puncture proof wheels
- Tamper foot widths (160-330mm)
- Tamper foot extensions
- h-/ rpm meter
- Special painting
- Tool kit
- Service Kit
- TOUGH WARRANTY



Dimensions in mm

	B	H	L	L1	W
BVT 65	350	1030	728	335	280

Technical Data

BOMAG
BVT 65

Weights

Operating weight CECE	kg	67
Basic weight	kg	66

Dimensions

Working width (tamper plate)	mm	280
------------------------------------	----	-----

Driving Characteristics

Working speed max.	m/min	20
Area coverage max.	m2/h	336

Drive

Engine manufacturer	Honda
Type	GX 100
Emission stage	Stage V / CARB P.3
Cooling	air
Number of cylinders	1
Performance SAE J 1349	kW 2,3
Fuel	Gasoline
Drive system	mech.
Fuel comsump. aver. during operation	l/h 0,9

Exciter system

Frequency	Hz	10- 11,8
Impact force	kN	16,0
Jumping height	mm	70,0

Capacities

Fuel	l	3,0
------------	---	-----

Technical modifications reserved. Machines may be shown with options.



PRE 541 21 010

210122 Sa02

BOMAG
Hellerwald
D-56154 Boppard
P.O. Box 5162
Tel. (0)6742 - 1000
Fax (0)6742 - 3090

